

KIT AC-MAX 2 DOORS

**Reference:** 5223

Access control kit for two doors. The kit consists of metal enclosure with power supply, networked access controller and IO expander. The controlled doors can be managed on both, input reader and output...

DESCRIPTION

Access control kit for two doors. The kit consists of metal enclosure with power supply, networked access controller and IO expander. The controlled doors can be managed on both, input reader and output reader side, by RS485 (FPAC-MAX), or Wiegand readers.

Each controlled door has separate 0.2 A supply output for readers and 1.0 A supply output for lock and other door equipment. The back-up battery charging current can be set to 0.3 A or 0.6 A. The entire system is supplied from the power supply included in the kit.

COMPOSITION:

-Metal BOX-IP15.

-PWR2D 13.8Vdc

-AC-MAX CU-2 central unit in TCP / IP network. It manages up to 2 doors each door with an input reader per door or with input reader and output reader per door, therefore it allows the connection of up to 4 Wiegand readers (2 input and 2 output) or 4 fingerprint readers FPAC-MAX (2 input and 2 output).

- EXT2D I / O expansion module.

TECHNICAL SPECIFICATIONS

Weight: 2,8698 kg

Size of product when packed: 10,5x30x30 cm

EAN 13: 8424299052236