

DATASHEET

TBK-MD5744

MAIN FEATURES



- HD 4 in 1.
- 2MP resolution.
- 2.8-12 mm varifocal lens.
- Sensitivity: 0,01 Lux (F1.2, AGC ON).
- 40 m IR range.
- OSD Menu.
- BLC.
- IP66, IK10.

Vandalproof minidome camera, with 2 megapixels resolution (1920x1080 at 25FPS). Varifocal 2,8-12 mm. HD 4 in 1 technology: switchable video signal output provides TVI/AHD/CVI/CVBS signal.




TBK-MD5744
SPECIFICATIONS

CAMERA	
Image Sensor	2 MP CMOS image sensor
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25 (1/30) s to 1/50,000 s
Lens	2.8 mm to 12 mm
Horizontal Field of View	111.5° to 33.4°
Lens Mount	Φ14
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°, Tilt: 0° to 75°, Rotation: 0° to 355°
Synchronization	Internal synchronization
Video Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
MENU	
AGC	High/Medium/Low/Off
D/N Mode	Auto/Color/BW (Black and White)
BLC	Support
DWDR	Support
Language	English
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
INTERFACE	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
GENERAL	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±15%
Power Consumption	Max. 4.2 W
Protection Level	IP66, IK10
Material	Metal
IR Range	Up to 40 m
Dimensions	∅ 130 mm × 143 mm (5.11" × 5.62")
Weight	630 g (1.39 lb.)



TBK-MD5744

DIMENSIONS

