



UAE 8 (8) Up 0
13010407

EAN: 4043921040683
 Farbe: pearl white (similar RAL 1013)

Performance features

Poles	8-way
Screw terminal	8
Spreading claws	•

Mechanical characteristics

General	
Operating temperature	-5 °C to +50 °C
Storage temperature	-5 °C to +50 °C
Protection class according to EN 60 529	IP20
Safety class according to DIN EN 61 140	II
Weight	44 g
Dimensions	
Width	70 mm
Height	70 mm
Depth	29 mm
Connector/outlet	
Design	DIN EN 60 603-7:1997-08
Connection technique	screw terminals for wires up to 1 mm Ø, 2 wires at each contact
Outlet universal use	for 6-way and 8-way plugs
Material spring contact	CuSn
Surface spring contact	1.5 µm Ni/1.3 µm Au
Material housing	PBT, POM, ABS
Life (cycles)	min. 2500 cycles

Electrical characteristics

Voltage	125 V DC
---------	----------

© 2009
 Specifications are subject to change
 Date: 19.06.2013

Niederwirth 1-10
 58579 Schalksmühle
 Phone (+49 2355) 82-0
 Fax (+49 2355) 82-105

www.rutenbeck.de
 mail@rutenbeck.de

Operation Current	max. 1 A at 50 °C
Voltage withstand	1000 V, 50 Hz, 1 min
Isolation resistance	> 500 MOhm
Contact resistance	< 20 mOhm

Transmission characteristics of the connectors/jacks

TIA/IAE-568-B.2-2001	Category 3
----------------------	------------
